



Mondraker Anark R

General Information		Bike Park
	Zero Suspension System	Fully
Technical Details	Rear derailleur: SRAM 70 Eagle, T-Type, 12-fach	Gear lever: SRAM Trigger 70, 12-fach, T-Type Actuation
frame: Anark 6061 Alloy Stealth Evo, 170mm Federweg	fork: RockShox ZEB Base Rush RC 29, 180 mm, konischer Gabelschaft,	weight: 17,8 kg
stem: ONOFF S6 30 mm 0°, geschmiedetes 6061 Aluminium + CNC	handle: ONOFF S6 1.0 7050 Aluminium, Erhöhung: 25 mm	brakes: SRAM DB8, 4-Kolben-Bremssattel, einteilige 200 mm IS 6-Loch
crank: SRAM 70 T-Type, Boost, DUB-Achse,	CASSETTE: SRAM XS-1270, 10-52Z, 12-fach	saddle: Ergon Enduro SPS20
Angle of seating: 74°	Seat post: X-Fusion Manic, Durchmesser 31,6mm	Length of chain stay: 445mm
Inner bearing lowering: -10mm	tyres: Maxxis Assegai 29 x 2,5 WT, Tubeless Ready,	length of cross bar: 583mm – 669mm
STACK: 644mm – 671mm	OFFSET: 44 mm	Length of head tube: 100 mm – 140mm
REACH: 440mm – 520mm	Diameter of seat post: 31,6 mm	Hight of inner bearing: 346mm
Width of handlebar: 800mm	Diamter of handlebar: 31,8 mm	Range of spring: 170 mm
Angle of handlebar: 63,5°	Length of seat tube: 380mm – 490mm	