



Mondraker Foxy

General Information	Size: 380mm-510mm	Enduro
	Forward Geometry	Fully
Technical Details	Rear derailleur: SRAM NX Eagle, 12-Gang, X-Actuation 1:1	Gear lever: Sram Trigger SX Eagle
frame: Foxy 29 6061 Stealth Evo Aluminium	fork: Fox 36 29 Float GRIP EVOL Rhythm, 160mm,	weight: 15,6 kg
stem: ONOFF Sulfur FG 30mm 0°, geschmiedetes 6061 Aluminium	handle: Onoff Sulfur 1.0, Erhöhung: 20mm	brakes: Sram G2 R, 4-Kolben Bremsattel, organische Bremsbeläge
crank: Sram SX Eagle, Boost, DUB Achse, Direct Mount Eagle, 170mm – 175mm	CASSETTE: Sram PG-1210, 11-50Z, 12-Gang	saddle: SDG BEL-AIR 3.0, LPU Schaum, Stahl Streben
Angle of seating: 71°	Seat post: Onoff Pija versenkbar, Durchmesser 31,6mm	Length of chain stay: 438/445mm
Inner bearing lowering: -22/-27mm	tyres: Maxxis Aggressor 29x2,3 WT, Tubeless Ready,	length of crossbar: 600mm – 670mm
STACK: 617mm – 647mm	OFFSET: 44 mm	Length of head tube: 100mm – 120mm
REACH: 445mm – 505mm	Diameter of seat post: 31,6 mm	Hight of inner bearing: 350mm
Width of handlebar: 800mm	Diameter of handlebar: 31,8 mm	Range of spring: 150 mm
Angle of handlebar: 64,5°	Length of seat tube: 375mm-500mm	