



## Mondraker Prime R

<b>General Information</b>	Size: S, M, L	Trail / E-MTB Trail
Fully integrated battery	Forward Geometry	Hardtail
<b>Technical Details</b>	Rear derailleur: SRAM SX Eagle, 12-Gang, X-Actuation 1:1	Gear lever: SRAM SX Eagle Single Click
frame: Prime 6061 Xtralite Aluminium konifiziert,	fork: RockShox 35 Silver TK 29, 44mm Offset	weight: 23,3 kg
stem: Onoff Sulfur FG 30mm 0°, geschmiedetes Aluminium	handlebar: Onoff Sulfur 1.0, Erhöhung: 20mm	brakes: Sram DB8, 4-Kolben Bremssattel, organische Bremsbeläge
crank: Race Face Aeffect e-Bike, 165mm	CASSETTE: Sram PG-1210, 11-50Z, 12-Gang	saddle: MDK e-Bike schwarz
DISPLAY: Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller	Seat post: Onoff Pija versenkbar, Durchmesser 31,6mm	battery: Bosch Powertube 750Wh
Lowering of inner bearing: -60mm	tyres: Maxxis Rekon 29x2,6, Tubeless Ready,	length of crossbar: 615mm – 670mm
STACK: 640 mm	OFFSET: 51 mm	Length of head tube: 110 mm – 130 mm
REACH: 425 mm – 480 mm	Diameter of seat post: 31,6 mm	Hight of inner bearing: 318mm
Width of handlebar: 800mm	Diameter handlebar: 31,8 mm	Range of spring: 120 mm
Angle of handlebar: 69°	Length of seating tube: 390mm – 470mm	Length of chain stay: 455mm
Angle of seating: 73,5°		