



Mondraker Superfoxy R

General Information	size: L, XL,	Super Enduro
	Forward Geometry	Fully
Technical Details	Rear derailleur: SRAM NX Eagle, 12-gear, X-Actuation 1:1	Gear lever: Sram Trigger SX Eagle
frame: Superfoxy 29 6061 Stealth Evo Aluminium	fork: Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube Kartusche	weight: 17,1 kg
stem: ONOFF Sulfur FG 30mm 0°, geschmiedetes 6061 Aluminium	handlebar: Onoff Sulfur 1.0, Erhöhung: 20mm	brakes: Sram DB8, oversized 4-Kolben Bremsattel, organische Bremsbeläge
crank: Truativ Descendant 7K Eagle, SuperBoost, DUB Achse, Direct Mount Eagle, 170mm – 175mm	CASSETTE: Sram XG-1230, 11-50Z, 12-Gang	saddle: SDG BEL-AIR 3.0, LPU Schaum, Stahl Streben
Angle of seating: 71°	Seat post: Onoff Pija versenkbar, Durchmesser 31,6mm	Length of chain stay: 445mm
Lowering of inner bearing: -20mm	tyres: Maxxis Assegai 29x2,5 WT, Tubeless Ready	Length of crossbar: 650mm – 670mm
STACK: 639mm	OFFSET: 44 mm	Length of head tube: 130mm
REACH: 490mm – 510mm	Diameter of seat post : 31,6 mm	Hight of inner bearing: 350mm
Width of handlebar: 800mm	Diameter of handlebar: 31,8 mm	Range of spring: 160 mm
Angle of handlebar: 65°	Length of head tube: 470mm-510mm	