



## Rotwild RC

<b>General Information</b>	Size: XL	Cross-Mountain E-Bike
removable battery	balanced weight distribution	Type: Fully
Brose Drive S Mag Motor		
<b>Technical Details</b>	Battery: IPU750 / 750 Wh	BB Drop: 35 mm
Brakes: MAGURA MT5 HC-W SHIFT MIX	Shock absorber: DT SWISS R535 ONE 185T X 55 mm / LINEAIR / INCONTROL	Display: BROSE DISPLAY ALLROUND BROSE APP / USB SPACER READY
Range of spring back: 142 mm	Range of spring front: max. 142 mm	Fork: DT SWISS F535 ONE 140 140 mm / APT, LINEAIR, COILPAIR / INCONTROL, PLUSHPORT
Cassette: SHIMANO CS 6100 10-51 T. / 12-SPEED	Length of chain stay: 460 mm	Crankset: E*THIRTEEN PLUS 170 mm (L, XL)
Charger: 4,5 A Ladegerät	Handlebar: ROTWILD B280 AL7075/ 35 mm RISE	Handlebar breadth: 780 mm
Handlebar diametre: 35 mm	Cross bar length: 688 mm	Frame: Vollcarbon, handgefertigt
Reach: 498 mm Radstand: 1289 mm	Tire back: max. 29x2.4 SCHWALBE NOBBY NIC EVO	Tire front: max. 29x2.4 SCHWALBE NOBBY NIC EVO
Saddle: ERGON SM	Seat tube length: 509 mm	Seatpost: CRANKBROTHERS HIGHLINE 3/ SETBACK / bis 150 mm
Seatpost dieamtre outside: 34,9 mm	Derailleur control: SHIMANO XT I-SPEC EV	rear derailleur: SHIMANO XT 8100 12-Speed
Stack: 649 mm Standover: 750 mm	Length of head tube: 140 mm	bottom bracket height: 340 mm
Angle of head tube: 66°, Angle of seat tube: 74°	Stem: ROTWILD S240 Ø35 mm / AL6061	Length of stem: 50 mm